

		ARGANO TIPO WINCH TYPE TREUIL TYPE GETRIEBE TYP			LEO			MOTORE - MOTORS - MOTEURS - MOTOREN			50 Hz.
								POLI POLES POLES POLEN	4/16	GIRI / 1' R.P.M. TOURS / 1' U / MIN	
HP	4,8	5,5	6,7	7,5				velocità speed vitesse geschw m / s	rapporto ratio rapport ubersetz.	puleggia sheave poulie treibsch. Ø mm.	
Kw	3,5	4,0	4,9	5,5							
DIFFERENZE DI TIRO - OUT OF BALANCE - FORCES DE TRACTION - ZUGKRAEFTE Kg	476							0,39	1/71	360	
	422							0,44	1/71	400	
	379							0,49	1/71	450	
	386	442	539					0,51	1/55	360	
	350							0,53	1/71	480	
	345	396	482					0,57	1/55	400	
	325							0,57	1/71	520	
	304							0,61	1/71	560	
	330	378	461	516				0,62	1/45	360	
	308	353	429					0,64	1/55	450	
	281							0,66	1/71	600	
	290	332	404					0,68	1/55	480	
	297	340	414	464				0,69	1/45	400	
	266	305	371					0,74	1/55	520	
	262	301	366	410				0,78	1/45	450	
	249	286	348					0,79	1/55	560	
	276	316	386	432				0,80	2/71	360	
	247	283	344	386				0,83	1/45	480	
	232	265	323					0,85	1/55	600	
	248	284	346	388				0,88	5/71	400	
	227	261	318	356				0,90	1/45	520	
	211	242	295	330				0,97	1/45	560	
	226	259	316	354				1,00	2/57	360	
	220	253	308	345				1,00	2/71	450	
	197	226	275	308				1,04	1/45	600	
	206	236	287	322				1,06	2/71	480	
	203	233	284	318				1,10	2/57	400	
	190	217	265	297				1,15	2/71	520	
	177	203	248	277				1,23	2/71	560	
	180	207	252	282				1,24	2/57	450	
	170	194	237	265				1,32	2/57	480	
	165	189	231	258				1,32	2/71	600	
157	179	219	245				1,43	2/57	520		
145	167	203	227				1,54	2/57	560		
136	156	190	212				1,65	2/57	600		
131	150	183	205				1,80	3/47	360		
118	135	165	184				2,00	3/47	400		
105	120	146	164				2,25	3/47	450		
98	112	137	154				2,40	3/47	480		
91	104	127	142				2,60	3/47	520		
84	96	118	132				2,80	3/47	560		
78	90	110	123				3,0	3/47	600		