


Flat trailing cables for lifts


Câbles flexibles pour ascenseurs

Cavi flessibili piatti per ascensori

CEI UNEL 73659



type - type - tipo		A07VVH2-F	
	<i>Characteristics</i> <i>Caracteristique</i> <i>Caratteristiche</i>	<i>Cables</i> <i>Câbles</i> <i>Cavi</i>	Cod.
Nominal tension U ₀ /U:	450/750 V.	24x1 (6x4)	CCPC-B24
Grado di isolamento U ₀ /U:		20x1 (5x4)	CCPC-B20
Max shifting rate:	6 m/s	16x1 (4x4)	CCPC-B16
Max velocità di spostamento:		12x1 (3x4)	CCPC-B12
Temperature	0°C - 40°C		
Temperatura			

type - type - tipo		H05VVH6-F	
	<i>Characteristics</i> <i>Caracteristique</i> <i>Caratteristiche</i>	<i>Cables</i> <i>Câbles</i> <i>Cavi</i>	Cod.
Nominal tension U ₀ /U:	300/500 V.	24x0,75 (6x4)	CCPC-A24
Grado di isolamento U ₀ /U:		20x0,75 (5x4)	CCPC-A20
Max shifting rate:	1,6 m/s	16x0,75 (4x4)	CCPC-A16
Max velocità di spostamento:		12x0,75 (3x4)	CCPC-A12
Temperature	0°C - 40°C		
Temperatura			