

		ARGANO TIPO WINCH TYPE MB 58 TREUIL TYPE MF 58 GETRIEBE TYP						MOTORE - MOTORS - MOTEURS - MOTOREN				50 Hz.	
								POLI POLES POLES POLEN	4/16	GIRI / 1' R.P.M. TOURS / 1' U / MIN	1500/375		
HP	7,5	8,2	10,0	12,5	15,0	17,5	21,0				velocità speed vitesse geschw m / s	rapporto ratio rapport ubersetz.	puleggia sheave poulie treibsch. Ø mm.
Kw	5,5	6,0	7,3	9,2	11,0	12,9	15,4						
DIFFERENZE DI TIRO - OUT OF BALANCE - FORCES DE TRACTION - ZUGKRAEFTE Kg	510	570	720					0,51	1/61	400			
	460	510	645					0,57	1/61	450			
	430	475	605					0,61	1/61	480			
	425	475	600	750				0,64	1/49	400			
	395	440	560					0,66	1/61	520			
	380	420	535	665				0,72	1/49	450			
	360	405	510					0,72	1/61	560			
	360	400	505	630				0,76	1/49	480			
	340	380	475					0,77	1/61	600			
	350	390	495	640	730				0,80	1/39	400		
	330	365	460	580				0,83	1/49	520			
	315	350	445					0,83	1/61	650			
	305	340	430	540				0,89	1/49	560			
	315	350	440	570	650				0,90	1/39	450		
	295	325	415	535	610				0,96	1/39	480		
	285	315	400	500					0,96	1/49	600		
	270	300	380	490	565				1,04	1/39	520		
	260	290	370	460					1,04	1/49	650		
	250	280	355	455	525				1,12	1/39	560		
	250	280	355	455	560				1,18	2/53	400		
	235	260	330	425	490				1,20	1/39	600		
	215	240	305	395	460				1,30	1/39	650		
	225	250	315	405	495	585			1,33	2/53	450		
	210	230	295	380	465	550			1,42	2/53	480		
	195	215	270	350	430	505			1,54	2/53	520		
	180	200	255	325	400	470			1,65	2/53	560		
	170	185	235	305	380	440			1,77	2/53	600		
	155	170	220	280	345	405			1,92	2/53	650		
	155	170	220	280	345	405	495			2,00	3/47	400	
	135	155	195	250	305	360	440			2,25	3/47	450	
130	145	180	235	285	340	410			2,40	3/47	480		
120	135	165	215	265	315	380			2,60	3/47	520		
110	125	155	200	245	290	355			2,80	3/47	560		
105	115	145	190	230	270	330			3,00	3/47	600		
95	105	135	175	210	250	305			3,25	3/47	650		