

		ARGANO TIPO WINCH TYPE TREUIL TYPE GETRIEBE TYP						<b>MB 82</b> <b>MF 82</b>		MOTORE - MOTORS - MOTEURS - MOTOREN				<b>50 Hz.</b>	
										POLE POLES POLES POLEN	4/16	GIRI / 1' R.P.M. TOURS / 1' U / MIN	1500/375		
HP	12,5	15,0	16,0	17,5	18,5	20,0	21,0	22,0	24,0	26,0	28,0	velocità speed vitesse geschw m / s	rapporto ratio rapport ubersetz.	puleggia sheave poulie treibsch. Ø mm.	
Kw	9,1	11,0	11,8	12,8	13,6	14,7	15,4	16,1	17,6	19,1	20,6				
DIFFERENZE DI TIRO - OUT OF BALANCE - FORCES DE TRACTION - ZUGKRAEFTE Kg	875	1055	1090									0,54	1/65	450	
	830	995	1030									0,57	1/65	480	
	760	920	950									0,62	1/65	520	
	710	850	955									0,67	1/52	450	
	715	850	880									0,67	1/65	560	
	660	795	895									0,72	1/52	480	
	660	795	820									0,72	1/65	600	
	645	775	830	915	975							0,73	1/48	450	
	605	725	775	860	915							0,78	1/48	480	
	605	730	825									0,78	1/52	520	
	605	730	755									0,78	1/65	650	
	570	680	720	800	850							0,84	1/48	520	
	565	675	765									0,84	1/52	560	
	565	675	700									0,84	1/65	700	
	530	635	715									0,90	1/52	600	
	525	630	655									0,90	1/65	750	
	540	645	690	760	815	885	930					0,91	1/39	450	
	530	635	670	740	790							0,91	1/48	560	
	505	605	645	715	765	835	875					0,96	1/39	480	
	490	590	615									0,96	1/65	800	
	485	580	620	685	730							0,98	1/48	600	
	485	580	660									0,98	1/52	650	
	470	560	600	665	705	770	810					1,04	1/39	520	
	450	540	610									1,05	1/52	700	
	445	535	575	635	675							1,06	1/48	650	
	435	520	555	615	655	720	750					1,12	1/39	560	
	420	505	570									1,13	1/52	750	
	415	500	535	590	625							1,14	1/48	700	
	390	475	530									1,20	1/52	800	
	405	485	515	570	610	665	715					1,21	1/39	600	
	385	465	495	550	585							1,22	1/48	750	
	360	435	465	515	550							1,30	1/48	800	
	375	450	480	530	565	615	645					1,31	1/39	650	
	395	475	505	560	600	650	690	725	800	825		1,33	2/53	450	
	350	415	445	495	525	575	600					1,40	1/39	700	
	370	445	475	525	560	610	645	680	750	775		1,42	2/53	480	
	325	385	415	460	490	535	560					1,51	1/39	750	
	340	410	435	485	515	565	595	625	690	715		1,54	2/53	520	
	305	365	390	430	460	500	525					1,61	1/39	800	
	320	380	410	450	480	525	555	585	645	665		1,65	2/53	560	
295	355	380	420	450	490	520	545	600	620		1,77	2/53	600		
285	345	370	410	435	480	505	530	585	640	690	1,81	2/39	450		
275	330	350	390	415	450	480	505	555	575		1,92	2/53	650		
270	325	345	385	410	445	475	500	550	600	650	1,93	2/39	480		
255	305	325	360	385	420	445	465	515	530		2,07	2/53	700		