

		ARGANO TIPO WINCH TYPE MB 82 TREUIL TYPE MF 82 GETRIEBE TYP						MOTORE - MOTORS - MOTEURS - MOTOREN				60 Hz.		
								POLI POLES POLES POLEN	4/16	GIRI / 1' R.P.M. TOURS / 1' U / MIN	1800/450			
HP	15,0	17,0	18,0	20,0	21,0	23,0	25,0	28,0	30,0	32,0	velocità speed vitesse geschw m / s	rapporto ratio rapport ubersetz.	puleggia sheave poulie treibsch. Ø mm.	
Kw	11,0	12,5	13,2	14,7	15,4	16,9	18,4	20,6	22,0	23,5				
DIFFERENZE DI TIRO - OUT OF BALANCE - FORCES DE TRACTION - ZUGKRAEFTE Kg	810	940									0,65	1/65	450	
	760	885									0,69	1/65	480	
	700	815									0,75	1/65	520	
	660	775	800								0,81	1/52	450	
	650	755									0,81	1/65	560	
	625	730	755								0,86	1/52	480	
	610	710									0,86	1/65	600	
	605	705	760	830							0,88	1/48	450	
	570	665	710	775							0,94	1/48	480	
	570	665	690								0,94	1/52	520	
	560	650									0,94	1/65	650	
	530	620	640								1,01	1/52	560	
	520	605									1,01	1/65	700	
	525	610	655	715							1,02	1/48	520	
	505	590	635	720	760	830					1,08	1/39	450	
	495	580	600								1,08	1/52	600	
	485	565									1,08	1/65	750	
	485	570	610	665							1,10	1/48	560	
	455	530									1,15	1/65	800	
	470	550	590	670	710	775					1,16	1/39	480	
	460	535	555								1,17	1/52	650	
	455	530	570	620							1,18	1/48	600	
	440	510	550	620	660	720					1,25	1/39	520	
	425	495	515								1,26	1/52	700	
	420	490	525	575							1,27	1/48	650	
	405	475	510	575	610	670					1,34	1/39	560	
	395	465	480								1,35	1/52	750	
	390	455	485	530							1,37	1/48	700	
	380	445	475	540	570	620					1,44	1/39	600	
	370	435	450								1,44	1/52	800	
	365	425	455	495							1,47	1/48	750	
	350	405	435	495	525	570					1,57	1/39	650	
340	400	425	465							1,57	1/48	800		
365	430	460	520	550	615	675	760			1,60	2/53	450		
325	380	405	460	490	530					1,69	1/39	700		
345	400	430	490	520	575	635	715			1,70	2/53	480		
300	350	380	430	455	495					1,81	1/39	750		
320	370	400	450	480	535	585	660			1,84	2/53	520		
285	330	355	400	425	465					1,93	1/39	800		
295	345	370	420	445	495	545	610			1,99	2/53	560		
275	320	345	390	415	460	505	570			2,13	2/53	600		
270	315	335	380	405	450	495	560	610	655	2,17	2/39	450		
255	295	320	360	380	425	470	525			2,31	2/53	650		
250	295	320	360	380	425	470	525	570	610	2,32	2/39	480		
235	275	295	335	355		435	490			2,48	2/53	700		