

		ARGANO TIPO WINCH TYPE TREUIL TYPE GETRIEBE TYP				MF 48				MOTORE - MOTORS - MOTEURS - MOTOREN				50 Hz.	
										POLE POLES POLES POLEN	4/16	GIRI / 1' R.P.M. TOURS / 1' U / MIN	1500/375		
HP	5,5	6,7	7,5	8,2	10					velocità speed vitesse geschw m / s	rapporto ratio rapport ubersetz.	puleggia sheave poulie treibsch. Ø mm.			
Kw	4,0	4,9	5,5	6,0	7,3										
DIFFERENZE DI TIRO - OUT OF BALANCE - FORCES DE TRACTION - ZUGKRAEFTE Kg	415	515	580	605					0,52	1/60	400				
	375	460	520	540					0,58	1/60	450				
	350	430	485	505					0,62	1/60	480				
	345	425	475	540	580					0,66	1/47	400			
	320	395	440	465					0,68	1/60	520				
	295	365	410	430					0,73	1/60	560				
	300	370	420	475	510					0,75	1/47	450			
	280	345	385	405					0,78	1/60	600				
	285	350	395	445	475					0,80	1/47	480			
	265	325	365	415	445					0,86	1/47	520			
	270	335	375	420	510					0,88	2/71	400			
	245	300	340	385	410					0,93	1/47	560			
	240	295	335	370	450					0,99	2/71	450			
	225	280	315	355	380					1,00	1/47	600			
	225	280	315	345	420					1,06	2/71	480			
	210	255	290	320	390					1,15	2/71	520			
	195	240	270	295	365					1,23	2/71	560			
	180	225	250	275	340					1,32	2/71	600			
	150	185	210	235	285					1,68	3/56	400			
	135	165	185	205	255					1,89	3/56	450			
125	155	175	195	235					2,01	3/56	480				
115	145	160	180	220					2,18	3/56	520				
110	135	150	170	205					2,35	3/56	560				
100	125	140	155	190					2,52	3/56	600				