

		ARGANO TIPO WINCH TYPE TREUIL TYPE GETRIEBE TYP				MF 48				MOTORE - MOTORS - MOTEURS - MOTOREN			60 Hz.	
										POLI POLES POLES POLEN	4/16	GIRI / 1' R.P.M. TOURS / 1' U / MIN		
HP	6,0	7,0	8,0	9,5	10					velocità speed vitesse geschw m / s	rapporto ratio rapport ubersetz.	puleggia sheave poulie treibsch. Ø mm.		
Kw	4,4	5,1	5,9	7,0	7,3									
DIFFERENZE DI TIRO - OUT OF BALANCE - FORCES DE TRACTION - ZUGKRAEFTE Kg	385	455	525	575					0,62	1/60	400			
	345	405	465	510					0,70	1/60	450			
	320	380	435	475					0,75	1/60	480			
	315	370	425	510	535					0,80	1/47	400		
	295	350	405	440					0,81	1/60	520			
	275	325	375	410					0,87	1/60	560			
	280	330	375	450	475					0,90	1/47	450		
	255	300	345	380					0,94	1/60	600			
	260	305	355	425	445					0,96	1/47	480		
	240	285	325	390	415					1,04	1/47	520		
	250	290	335	405	425					1,06	2/71	400		
	225	265	305	365	385					1,12	1/47	560		
	220	260	300	360	380					1,19	2/71	450		
	210	245	285	340	355					1,20	1/47	600		
	205	245	280	335	355					1,27	2/71	480		
	190	255	260	310	325					1,38	2/71	520		
	175	210	240	290	305					1,48	2/71	560		
	165	195	225	270	285					1,59	2/71	600		
	140	165	190	225	240					2,01	3/56	400		
	125	145	165	200	210					2,27	3/56	450		
115	135	155	185	200					2,42	3/56	480			
105	125	145	175	180					2,62	3/56	520			
100	115	135	160	170					2,82	3/56	560			
90	110	125	150	160					3,02	3/56	600			